



Zexel/ Valeo	
125 ml (4.4 fl. oz.)	1161 627
Visteon	
125 ml (4.4 fl. oz.)	1161 627
Sanden	
125 ml (4.4 fl. oz.)	1161 629
Seiko-Seiki	
125 ml (4.4 fl. oz.)	1161 628

A synthetic PAG compressor oil intended for AC compressors which use R134a.

The oil is sold with different part numbers, depending on the make of compressor.

Since the oil is strongly hygroscopic (absorbs water), opened packages should be used up at once.

Technical data

	627	628	629
Density at 15°C (59°F):	1005 kg/m³	1024 kg/m³	1018 kg/m³
Base:	Polyalkylene glycol	Polyalkylene glycol	Polyalkylene glycol
Lowest flow point:	-50°C	-45°C	-50°C
Flash point:	+232°C	+244°C	+250°C
Viscosity at 40°C:	45.36 mm²/s	95.60 mm²/s	98.77 mm²/s
Viscosity at 100°C:	9.948 mm²/s	19.28 mm²/s	19.56 mm²/s

Oil, AC compressor

— R134a

1837

Model:	Engine:	Model year:	Oil, AC compressor R134a:
240	All	93	1161 628
400	All	94-97	1161 627
850	All	All	1161 627
940	All	93-95	1161 628
940/960/S90/V90	All	96-98	1161 627
S40 -04, V40	All gasoline except B4184SM/SJ (GDI)	All	1161 627
S40 -04, V40	B4184SM/SJ (GDI)	All	1161 628
S40 -04, V40	All diesel	All	1161 629
S60/ S80 -06/ V70 00-/V70XC 01-/XC70/XC90	All	All	1161 627
S40 04-/V50/C70 06-/C30	All 5-cyl	All	1161 627
S40 04-/V50/C30	All 4-cyl gasoline	All	1161 627
S40 04-/V50/C30	All 4-cyl diesel	All	1161 629